




LED Transparent Screen | Vclear-Pro Rental Series

Leyard Vteam transparent led display is a kind of innovative transparent led display, with transparent, novel structural, HD high brightness, simple application, intelligent control, energy saving and environmental, novel imaging features etc. Vclear-pro rental series is widely used in TV shows, concerts and large entertainment programs, auto shows and high terminal exhibition and other kinds of scenes, to achieve a novel and unique scene application.

Front-emitting, >70% Transparency

No front and back PC mask
Special buckle to protect led strips
No sun/light reflection



Spray Type Waterproof Structure

No traditional pouring and GOB sealing process, easy maintenance, good heat dissipation, no color difference.



High Contrast

High contrast 2500:1, rich color, Materials and images Stage effect is better



Fast Installation | Thin and Light

As light as 12.5kg/m², the cabinet integrates the double function design of fast lock and handle, easy to installation



Front-maintenance Module

No screws, special quick maintenance lock, convenient maintenance and disassembly



Dislocation Installation

Diversified artistic shapes
More novel visual experience





Cabinet Dimension

1000 x 500 x 82mm

Application scenarios

Commercial center, stage choreographer, advertising media, Exhibition display

Vclear-Pro (Outdoor Rental Series)

- Application environment : Indoor and outdoor
- Life Span : $\geq 100,000$ hours
- Cabinet material: magnesium alloy and aluminum alloy optional
- Installation method : Hanging / fixed
- Certification : CE / FCC



Light transmission



colorful



Anti-vibration port



Anti-Knock lamp design



Modular



Mixed batch use



140° Wide viewing angle



Stable system

Model	Vclear Pro-3.9	Vclear Pro-7.8	Vclear Pro-10.4
Pixel Pitch (H/V)	3.9 / 7.8mm	7.8mm	10.4mm
LED Configuration	SMD 1921	SMD 1921	SMD 1921
Brightness(CD/m ²)	3500 ~ 4000	3500 ~ 4000	3500 ~ 4000
Pixel Density(Dot/m ²)	32256	16384	9216
Transparency	$\geq 48\%$	$\geq 48\%$	$\geq 70\%$
Cabinet Resolution(Dot)	252 x 64	128 x 64	96 x 48
Cabinet Weight(/Panel)	6.2kg	6.2kg	6.2kg
Ingress Protection(Front/Back)	IP54	IP54	IP54
Viewing Distance	>4m	>8m	>10m
Gray Scale	14 bit	14 bit	14 bit
Max.Power Consumption(W/m ²)	480	480	490
Avg.Power Consumption(W/m ²)	192	192	196
Refresh Rate(Hz)	≥ 1920	≥ 1920	≥ 1920
Drive Mode	7S	4S	3S
Input Voltage	AC100 ~ 240V, 50 / 60 Hz		
Control Mode	Synchronous display with control PC by DVI		
Signal Input	Composite, S-Vido, Component, VGA, DVI, HDMI, HD_SDI		
Operating Temperature	0° C ~ 40° C (work) , - 20° C ~ 60° C (store)		
Operating Humidity	35% ~ 85% (work) , 10% ~ 90% (store)		
Packaging	Flight case		